HARWI ORCA Vertical panel saw





HARWI ORCA

Vertical panel saw


BASIC - PREMIUM - PRO

HARWI ORCA

The **Harwi Orca** panel saw is an excellent choice when you are dealing with an intensive sawing process that requires high accuracy. The ORCA is standardly equipped with a **powerful 4kW** electric motor

that indirectly drives the sawing blade speed at 5000 rpm. The **strong welded frame** construction and stable sawing beam ensures a perfect cut. Due to its maintenance friendly character and long lifespan, **interior builders & carpentry factories** have been charmed by our ORCA machines for many years.

The Harwi Orca is available in a **Basic, Premium & Pro** version.



Specifications

| Туре | Harwi Orca basic | Harwi Orca premium | Harwi Orca pro |
|--------------------------|------------------------|--------------------|-------------------|
| Height of cut horizontal | 1250/1550/1850/2150 mm | 1550/1850/2150 mm | 1550/1850/2150 mm |
| Height of cut vertical | 1300/1600/1900/2200 mm | 1600/1900/2200 mm | 1600/1900/2200 mm |
| Length of cut | 2500/3300/4300/4300 mm | 3300/4300/4300 mm | 3300/4300/4300 mm |
| Depth of cut | 55 mm | 55 mm | 55 mm |
| Diameter saw blade | ø 250 mm | ø 250 mm | ø 250 mm |
| Diameter scoring saw* | n.v.t. | n.v.t. | ø 70 mm |
| Motor Power | 4 kW (5.5 pk) | 4 kW (5.5 pk) | 4 kW (5.5 pk) |
| Voltage | 400V/3~ | 400V/3~ | 400V/3~ |
| Spindle speed | 5000 rpm | 5000 rpm | 5000 rpm |
| Scoring saw rpm* | n.v.t. | n.v.t. | 13000 rpm |
| Diameter dust extraction | ø 100 mm | ø 100 mm | ø 100 mm |







"All Orca models come standard with an electrical moving back panel "

| Model specificaties | Harwi Orca basic | Harwi Orca premium | Harwi Orca pro |
|---|------------------|--------------------|----------------|
| Electrical moving Back panel | \checkmark | \checkmark | \checkmark |
| Length stop analog | \checkmark | \checkmark | \checkmark |
| Power supply 220V for extraction system | \checkmark | \checkmark | \checkmark |
| Panel mover | \checkmark | \checkmark | \checkmark |
| Midway fences* | \checkmark | \checkmark | \checkmark |
| Electro Clamping Horizontal | \checkmark | \checkmark | \checkmark |
| Transportrollers Pneumatic | Х | Х | \checkmark |
| Transportrollers foot operated | 0 | \checkmark | Х |
| TRK Dust extraction horizontal | Х | \checkmark | \checkmark |
| Reiteration stop | \checkmark | \checkmark | \checkmark |
| Stops for horizontal cuts | Х | \checkmark | \checkmark |
| Support midway fence | Х | \checkmark | \checkmark |
| Length stop guiding block | Х | \checkmark | \checkmark |
| Digital read out horizontal/ vertical | Х | 0 | \checkmark |
| Scoring saw | Х | Х | \checkmark |

✓ = standard X = not possible O = Optional / * Midway fences: basic maximum - Premium maximum- Pro maximum

Information regarding machine measurements and weigths please contact our sales department



Our mission

Through combining experience and craftsmanship with service and development, we strive for an optimal working environment in which safety, ergonomics and health come first.

The robust nature and the long service life of our machines characterize our passion for technology. Our core business is the delivery of standard sawing solutions in the wood industry. However we also us our expertise and knowledge to aid our customers in process specific sawing solutions.

Our company

Harwi has been producing its sustainable sawing machines in Helmond in Brabant since 1960. Our specialization and expertise in the wood industry in particular has been ensuring satisfied customers for years.

Providing innovative sawing solutions within the Netherlands and abroad is the foundation of our organization. Within this foundation we priorities user friendliness and quality.

Check all our machines and options

www.harwi.nl

Harwi Holland BV Lage Dijk 28

5705 BZ Helmond Nederland

T +31 (0)492 54 33 55 sales@harwi.nl www.harwi.nl

